

MP Antenna, LTD. 147 Eady Court Elyria, Ohio 44035

440.387.5968 phone 440.545.3500 fax www.mpantenna.com sales@mpantenna.com

Part Number: MP-R-5XB-12233-USB-M

model number: MP-R-5XB-12233-USB-M

product description: Multi-Band Omni Rugged WiFi Antenna

## **Electrical Data**

## **Environmental Data**


frequency range:	2-3GHz, 4.9-6GHz, GPS	environmental cond.:	Outdoor
gain:	6dBi	operation temperature:	-40 to 85 deg C
vswr:	<1.5:1	storage temperature:	-40 to 85 deg C
horizontal pattern type:	Omni Directional	transport temperature:	-40 to 85 deg C
vertical patter type:	Hemispheric	IP Rating:	IP67
ground plane:	Built In	Rohs - Reach	Compliant
min ground plane:	N/A		

## **General Data**

## **Mechanical Data**

color:	Black	length:	11.8 in
antenna feeds:	Five	width:	9.6 in
coax length:	N/A	radome height:	3.1 in
coax type:	N/A	weight:	4 lbs
connector type:	N-Female	hardware included:	N/A
polarization:	Multi-Polarized		
power:	50 Watts Input		
impedance:	50 ohms Nominal	* With built in spatial and polarization diversity, performance in obstructed environments is	
construction:	Impact Resistant Delrin		
		greater than that of s similar or higher labo	standard antennas with oratory gains.







440.387.5968 phone 440.545.3500 fax www.mpantenna.com sales@mpantenna.com




Part Number: MPSL4400-6000-BL-B

model number: MPSL4400-6000 product description: 4.4-6 GHz Omni

Frequency Feed One, Two: 2.45 GHz

Max Gain: 6dBi



Frequency Feed Three and Four: 4.95 GHz

